




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC.. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	4/6/12	D.GRIFFIN



RECOMMENDED STRIPPING DIMENSIONS

NOTES:

MATERIAL: NICKEL PLATED BRASS.

CONNECTOR ASSEMBLY POLISH TYPE: PC.



MODEL IS NON-LOCKING STYLE, MULTIMODE.

STRIP FIBER CABLE TO MIL-STD-2042-5B. STRIP DIMENSIONS ARE +/- 1mm.

DUST CAP IS INSTALLED FOR SHIPMENT.

COMPONENTS COME UNASSEMBLED AND SHALL BE INDIVIDUALLY PACKAGED IN A POLY BAG.

RoHS Compliant ✓

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 .XX = ± .02 .XXX = ±.005	APPROVALS		DATE		 <div>45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845</div>	
	DRAWN BY D.FRISIELLO		2/24/12			
	CHECKED BY D.GUITADAURO		2/24/12			
	APPROVED BY D.GALLAGHER		2/24/12			
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY				FIBER OPTICS PRODUCT DESCRIPTION MIL ST MM NON-LOCK NPB 2MM	
	COLOR VARIATIONS MAY OCCUR					
	SIZE A	FSCM NO. 43321	DWG. NO. FOC-M83522-DNXB			REV. A
	SCALE: NONE		CAD FILE: FOC-M83522-DNXB.SLDDRW			SHEET 1 OF 1